



MP-52 Clippership Bituminous Joint Compound

Product Data Sheet

Product Highlights

Solids:

> 70 %

Application Rate:

25 Square Feet per Gallon.

Specification:

ASTM D2822

State DOT Approved

Application Surfaces:

Multiple Surfaces

Application Temperature Range:

No service air application
temperature restrictions.

SEABOARD ASPHALT
PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, MD 21226

1-800-536-0332

1-410-355-0330

Product Description:

Clippership Bituminous Joint Compound is a trowel mastic asphaltic compound for joint sealing.

Basic Uses:

Clippership Bituminous Joint Compound is used as a joint sealant for concrete pipe, foundations, and all other masonry and steel joint sealing.

Storage and Limitations:

- Do not heat container.
- Protect the container from weathering.

Application:

Clippership Bituminous Joint Compound can be applied by trowel in a liberal fashion to fill the joint completely. This material can be applied year round.

Coverage:

25 Square Feet per Gallon.

Composition and Safety:

For complete safety information please review the Safety Data Sheet for this product.

Revision Date: 02/2016

This information is to assist customers in determining if this product is suitable for the proposed application, and to satisfy themselves as to suitability of the contents. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from law or patent implied.